



## DECLARATION OF PERFORMANCE

Nro. 200-FF-2020-03-03

1. **Unique identification code of the product-type:** Polyisocyanurate board (PIR) FF-PIR xxx FRK / FRL / FRI
2. **Allowing identification of the construction product:** See product label.
3. **Intended uses of the construction product:** Products are used as thermal insulation. Product applications are specified in the web site [www.finnfoam.fi](http://www.finnfoam.fi).

4. **Name, registered trade name and contact address of the manufacturer:**

Finnfoam Oy (0689386-6)  
Satamakatu 5  
24100 Salo, Finland  
Tel. +358 2 777 300  
Fax: +358 2 777 3020  
Email: [finnfoam@finnfoam.fi](mailto:finnfoam@finnfoam.fi)

6. **System of attestation of conformity:** AVCP 1 for reaction to fire and AVCP 3 for other characteristics.

7. **Declaration of performance concerning a construction product covered by a harmonized standard:** Eurofins Expert Services (NB. 0809) and Institute of thermal insulation of Vilnius Gediminas Technical University (NB. 1688) performed initial type testing and VTT Expert Services (NB.0809) made Initial inspection of factory and of FPC by system 1 and draw up a certificate of conformity nro.0809 -CPR -1185.

**8. Declared performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	Euroclass	B-s1, d0 (black side of board) NPD (light side of the board)	EN 13165:2012 + A2:2016
	Foam fireclass VTT-C-11858-16	D-s2,d0	
Water permeability	Long term water absorption by total immersion	NPD	
	Flatness after one-sided wetting	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	No harmonised test method available	
Acoustic absorption index	Sound absorption	NPD	
Direct airborne sound insulation index	Sound absorption	NPD	
Continuous Glowing combustion	Continuous Glowing combustion	No harmonised test method available	
Thermal resistance	Thermal conductivity $\lambda_D$	< 80 mm: 0,027 80 – 119 mm: 0,026 $\geq$ 120 mm: 0,025	
	Thickness tolerance	T2	
	Thickness (mm)	Thermal resistance (m <sup>2</sup> K/W)	
	60	2,20	
	70	2,60	
	100	3,10	
	110	3,85	
	120	4,25	
	130	5,20	
	140	5,60	
	150	6,00	
	160	6,40	
180	7,20		
200	8,00		

Water vapour permeability	Water vapour transmission	NPD
Compressive strength	Compressive strength	CS(10/Y)100
Tensile/flexural strength	Tensile strength perpendicular to faces	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability of reaction to fire of the product as placed on the market against ageing/degradation	No change in Reaction to fire properties for rigid polyurethane foam products.
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensional stability under specified temperature and humidity conditions	DS(70,90)4
		DS(-20,-)2
	Deformation under specified compressive load and temperature conditions	NPD
		NPD
Durability of compressive strength against ageing/degradation	Compressive creep	NPD

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Safety data sheet: [www.finnfoam.fi/kayttoturvallisuustiedote](http://www.finnfoam.fi/kayttoturvallisuustiedote)**

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 3.3.2020



\_\_\_\_\_  
(Signature)